

Description

The AquiTron™ AT- LDM offers a low cost option for liquid leak detection. It is designed for use with all TraceTek sensing cables, AquiTron™ probes and other sensing devices to detect leaks. The AT-LDM provides visual indication when a leak has occurred and has relay contacts to connect to other external alarm equipment. An option is available with an audible alarm.

Each module comes in two forms; either with DIN rail mounting frame or polycarbonate enclosure together with comprehensive installation instructions.

Simple Operation

Two LED's to indicate the operating status of the unit:
 POWER – alarm unit power (green)
 LEAK – liquid detected (red)

Application

Primarily designed for small area detection in locations such as Tea Points, Kitchens, Bunded area's and Drip Trays, or alternatively these units can be used with the AquiTron™ AT-RWS-1 Rain Sensor.

Because of their compact size these modules can normally be easily incorporated into OEM equipment or outstation enclosures thus saving the cost of a dedicated enclosure.

Modules can be sited close to the area to be monitored or mounted up to 200 metres away in control equipment.

AT-LDM-SM housed in a polycarbonate enclosure



AT-LDM & AT-LDM-S open chassis, DIN rail mounting



Technical Information

Sensing cable compatibility	All TraceTek adapted sensing cable (TT1000, 3000, 5000, 5001 and 7000)
Detection Probes	Water detection probes, optical oil sensors, float switches and immersion sensors
Maximum length of sensing cable	45 metres (150 ft)
	Combination of any 10 AquiTron™ probes
Enclosed version	Polycarbonate; smoked transparent lid, base & grey base; IP 66
Operating Conditions (PCB)	-10 to +50 °C, 0% to 90% non-condensing
Power supply	Two versions: 24V ac/dc & 230Vac (ac 50/60Hz)
Power consumption	50 mA @ 24V ac/dc and 11mA @ 230Vac
Relay Output	Volt free relay contacts activated by leak SPDT (NC/COM & NO)
Relay Rating	5 A at 250 Vac/24 Vdc
Status LED	Power (Green), Leak (Red)
Audible Alarm	85dB 10cm (where fitted)
Dimensions	Open chassis: 77mm x 112mm x 45mm Enclosed: 130mm x 130mm x 75mm
Weight	Open chassis: 82g ~ 24V version & 248g ~ 230V version Enclosed: 660g

Approvals

Electromagnetic compatibility (EMC)



Ordering information	Catalogue number	4200	AT-LDM	Open Chassis: 24Vac
		4205	AT-LDM-S	Open Chassis: 24Vac with sounder
		4210	AT-LDM	Open Chassis: 230Vac
		4215	AT-LDM-S	Open Chassis: 230Vac with sounder
		4220	AT-LDM-SM	Enclosed: 230Vac with sounder & mute

Operational Notes

All Modules are Auto Reset and the relay contacts will remain activated as long as the sensor is wet.

On Modules with sounders fitted the sounder can be temporarily silenced by removing a link on the open chassis version or operating the switch on the enclosed versions

Important: All information, including illustrations, is believed to be reliable. Users, however, should independently evaluate the suitability of each product for their application. Aquilar Limited makes no warranty as to the accuracy or completeness of the information, and disclaims any liability regarding its use. The only obligations of Aquilar Limited are those in the Aquilar Standard Terms and Conditions of Sale for this product, and in no case will Aquilar Limited be liable for any incidental, indirect, or consequential damages arising from the sale, resale, use or misuse of the product. Specifications are subject to change without notice. In addition, Aquilar Limited reserves the right to make changes – without notification to Buyer – to processing or materials that do not affect compliance with any applicable specification.

Aquilar is a trademark of Aquilar Limited
AquiTron is a trademark of AquiTron Limited
TraceTek is a trademark of Tyco Thermal Controls.

Aquilar Limited

Dial Post Court, Horsham Road,
Rusper, West Sussex RH12 4QX. UK
Tel: + 44 (0) 1293 871874
Fax: +44 (0) 8707 940 320

E-mail: info@aquilar.co.uk
www.aquilar.co.uk

Master TraceTek Distributor UK & Ireland for
Raychem® TraceTek®
Water, Fuel and Chemical Leak Detection