



# AT-G-DETECT Airflow / Duct Mount Sensor Housing



## AT-G-DETECT IP66 Airflow / Duct Mount Sensor Housing

The airflow duct mount sensor has been designed to monitor airflows or ducts while allowing easy access to the sensor for maintenance.

It is mounted on the outside of the duct and a pitot type sample tube extends into the duct. The airflow goes in one leg of the pitot up into the sensor box, where the sensor head lies and back out into the duct.

Typically they are used to monitor refrigerant leaks in air conditioning systems or any gas in an airflow.



### Dimensions and Weight

IP66 Enclosure  
175 x 125 x 82mm – 553g  
6.8 x 4.9 x 3.2 inches – 1.2lbs

Pitot tube length  
193mm, 7.68 inches

Important: All information, including illustrations, is believed to be reliable. Users, however, should independently evaluate the suitability of each product for their application. Aquilar Limited makes no warranty as to the accuracy or completeness of the information, and disclaims any liability regarding its use. The only obligations of Aquilar Limited are those in the Aquilar Standard Terms and Conditions of Sale for this product, and in no case will Aquilar Limited be liable for any incidental, indirect, or consequential damages arising from the sale, resale, use or misuse of the product. Specifications are subject to change without notice. In addition, Aquilar Limited reserves the right to make changes – without notification to Buyer – to processing or materials that do not affect compliance with any applicable specification.

Aquilar is a trademark of Aquilar Limited  
AquiTron is a trademark of AquiTron Limited