



TT-FFS Probe Tester

Test Device for TT-FFS Probe

Simple Tool

The TT-FFS Probe Tester is a battery powered device that provides the capability of testing a TT-FFS Probe to determine whether it is functioning properly.

The TT-FFS Probe Tester is designed for use in ordinary areas.

For a TT-FFS Probe with MC series metal connector, the TT-FFS Probe Tester is directly connected to the TT-FFS Probe. For a TT-FFS Probe without metal

connector (L series), the TT-FFS-ALLIGATOR4CLIP-MC cable end adaptor is attached to the TT-FFS Probe Tester. The 4 colored alligator clip wires are connected to the corresponding colored wires of the TT-FFS Probe.

Visual Indication

The TT-FFS Probe Tester produces flashing signals using bright red LEDs that indicate different operational conditions of the TT-FFS Probe. The TT-FFS Probe Tester also monitors its battery voltage and produces a special flashing signal to indicate that the voltage is low and the batteries need replacing.



Ordering Information

Catalog Number	P/N	Description
TT-FFS Probe Tester	P000001048	Battery powered device used to evaluate TT-FFS Probe operational state. Includes TT-FFS-ALLIGATOR4CLIP-MC cable end adaptor for use with TT-FFS Probe without metal connector (L series)

Product Characteristics

Weight	0.3 kg (0.7 lb) nominal
Light source	3 high intensity, high efficiency red LEDs
Battery information	2 "AA" Alkaline Long Life
Projected battery life	1 year – nominal
Recommended battery replacement interval	1 year or whenever low battery signal is detected
Duration of low battery signal	Minimum 30 days at 20°C (68°F)
Maximum ambient temperature	40°C (104°F)
Minimum ambient temperature	-20°C (-4°F)

Tyco and TraceTek are trademarks of Tyco Thermal Controls LLC or its affiliates.

Worldwide Headquarters
Tyco Thermal Controls
 307 Constitution Drive
 Menlo Park, CA 94025-1164
 USA
 Tel (800) 545-6258
 Tel (650) 216-1526
 Fax (800) 527-5703
 Fax (650) 474-7215
 info@tracetek.com
 www.tracetek.com

Important: All information, including illustrations, is believed to be reliable. Users, however, should independently evaluate the suitability of each product for their particular application. Tyco Thermal Controls makes no warranties as to the accuracy or completeness of the information, and disclaims any liability regarding its use. Tyco Thermal Controls' only obligations are those in the Tyco Thermal Controls Standard Terms and Conditions of Sale for this product, and in no case will Tyco Thermal Controls or its distributors be liable for any incidental, indirect, or consequential damages arising from the sale, resale, use, or misuse of the product. Specifications are subject to change without notice. In addition, Tyco Thermal Controls reserves the right to make changes—without notification to Buyer—to processing or materials that do not affect compliance with any applicable specification.