



Tape 0.79 thick with protective overlay

Product Code	A	B	C	Maximum Wire size Diameter D	Rated Static Load N
TT-HDC-1/4 – xx					
xx = 50 or 200	25.40	38.10	8.64	6.35	5.00

Material: PVC

Available in Clear only

Tolerances: All dimensions: $\pm .76$

Rated static loads apply for parts fastened to a flat, clean, dry surface and used within a temperature range of -29°C to 65°C

Recommended installation temperatures are 15°C to 27°C

Flame retardant PVC, UL 94V-0

- **Low profile**
- **Easy cable installation**
- **Clear PVC extruded body**
- **Self extinguishing**

Important: All information, including illustrations, is believed to be reliable. Users, however, should independently evaluate the suitability of each product for their application. Aquilar Limited makes no warranty as to the accuracy or completeness of the information, and disclaims any liability regarding its use. The only obligations of Aquilar Limited are those in the Aquilar Standard Terms and Conditions of Sale for this product, and in no case will Aquilar Limited be liable for any incidental, indirect, or consequential damages arising from the sale, resale, use or misuse of the product. Specifications are subject to change without notice. In addition, Aquilar Limited reserves the right to make changes – without notification to Buyer – to processing or materials that do not affect compliance with any applicable specification.

Aquilar is a trademark of Aquilar Limited
AquiTron is a trademark of AquiTron Limited

Aquilar Limited
Weights & Measures House, 20 Barttelot Road,
Horsham, West Sussex RH12 1DQ. UK
Tel: + 44 (0) 1403 216 100
Fax: +44 (0) 8707 940 320

E-mail: info@aquilar.co.uk
www.aquilar.co.uk

