

AquiTron

AT-SRG

Sensor for
Refrigerant Gas



DATA SHEET



aquilar
leak detection solutions



AT-SRG

Sensor for Refrigerant Gas - Occupied Spaces

The Aquitrone AT-SRG refrigerant gas sensor, designed for continuous monitoring in occupied spaces, particularly those with high-efficiency VRF/VRV cooling and heating systems. Its applications include hotels, offices, schools, server / comms rooms, dormitories, hospitals, homes, and apartments.

SIMPLE OPERATION

The AT-SRG comes equipped with audible and visual alarms to alert occupants and seamlessly communicates with Building Management Systems (BMS). It can be directly linked to Eco range panels for centralised monitoring and alarms. The on-board volt free relay facilitates various functions, including pump down, activating alarms, exhaust fans, or remote initiating emergency calls to rescue teams.

VERSATILE DESIGN

The AT-SRG has been designed to be installed and maintained easily, and included the following features:

- 15 year expected sensor head life span.
- Compact UK single gang electrical socket size for an aesthetically-pleasing, non-intrusive appearance.
- Simple installation, set-up and commissioning as no calibration required.
- Easy system testing with a plug-in alarm emulation module (no gas required).
- Multiple alarm outputs, audible and visual on high and low level concentrations (two alarm levels),.
- Mains and low voltage power options.
- Easy sensor replacement (plug & play) with interchangeable sensor heads for different gas types.
- Flush mount fascia available in standard finishes: RAL9016 ABS Gloss White Finish and Brushed Stainless Steel. (for special or bespoke face plate fascias please contact us)
- Refrigerant specific sensor, immune to poisoning and reacts only to target gas with automatic temperature and humidity compensation
- Switchable delay to avoid false alarms.
- Enhanced connectivity for remote and central alarm using either volt free relay (1x) for centralised and BMS monitoring. or direct connection to one of our ECO range panel.
- Fully compatible with the AquiNet central monitoring system where compliance to BS EN378 is required.

APPLICATIONS

The sensor is essential as part of a life safety system for continuous monitoring of refrigerant gas leaks from air conditioning and heat pump systems and is designed to safeguard people in occupied spaces within residential and commercial buildings such as hotels, apartments, hospital rooms and offices. Suitable for single to large multi-zone installations. It's crucial to prioritise the safety of your systems, implement sufficient monitoring measures, and ensure compliance with regulations—all while managing costs effectively.

Sensor to help achieve compliance, BS EN 378, BREEAM POL1, F-GAS.

TECHNICAL INFORMATION

Detectable Gases	R-410a, R-32, and R-290**
Trigger Values	Two alarm levels - R410 - Low Level 2000ppm - High Level 8000ppm Two alarm levels - R-32 & R-290** - Low Level 10% LEL - High Level 15%
Housing	Flush mount or surface mount available
Dimensions	Body: 79.5mm x 79.5mm x 28mm (WxHxD) 4667 - Faceplate White Plastic: 86 x 86 x 4mm (WxHxD) 4666 - Faceplate Brushed Stainless Steel: 86 x 86 x 2mm (WxHxD) 4670 - 44mm Deep Surface Enclosure (35mm minimum) : 86 x 86 x 50mm (WxHxD)
Protection	Indoor: IP20
Power Supply	100-240 Vac, 50/60Hz 1 Watt Max 12 / 24 Vac/dc 1 Watt Max
Relays	1x SPDT Max Load - 3A at 30Vdc, 3A at 250Vac
Audible Alarm	67 dB at 1Meter
Alarm Delay	0 or 5 minutes. Selectable.
Recommended Cable Sizes	Power 230Vac: 3-core 1.5mm ² recommended Power 12/24Vac/dc: 2-core 1.5mm ² recommended Relay: 3-core, 1.5mm ² recommended
Environmental Operating Range	Operating Temperature: -25°C - 50°C Storage Temperature: -25°C - 40°C Humidity: 5 - 85% RH, Accuracy guaranteed in non-condensing environments Pressure: 80 - 120 kPa
Status LED	Bi colour LED: Green and Red
Sensor Life	15 year expected minimum life dependant on environment with recommended 6 month testing

** available Q1 2024

APPROVALS

Electromagnetic compatibility (EMC)



BS EN IEC 61000-6-3:2021
BS EN IEC 61000-6-1:2019

ORDERING INFORMATION

Catalogue numbers	4662 - AT-SRG-12/24-R410A - Sensor for Refrigerant Gas within occupied spaces, R410A, 12/24V ac/dc, No Faceplate
	4678 - AT-SRG-12/24-R32 - Sensor for Refrigerant Gas within occupied spaces, R32, 12/24V ac/dc, No Faceplate
	4679 - AT-SRG-12/24-R290 - Sensor for Refrigerant Gas within occupied spaces, R290, 12/24V ac/dc, No Faceplate **
	4661 - AT-SRG-230-R410A - Sensor for Refrigerant Gas within occupied spaces, R410A, 230Vac, No Faceplate
	4668 - AT-SRG-230-R32 - Sensor for Refrigerant Gas within occupied spaces, R32, 230Vac, No Faceplate
	4669 - AT-SRG-230-R290 - SSensor for Refrigerant Gas within occupied spaces, R290, 230Vac, No Faceplate **

Please specify the following when ordering:

- Flush mount or surface mount
- Flush mount fascia finish options - ABS white, brushed stainless steel. **Bespoke finishes also available to special order.**
- Surface mount is available in white only
- Refrigerant gas type, R410A, R32 and R290.

** Available Q1 2024

ANCILLERY PRODUCTS

4667 - AT-SRG-SGFP-W - Faceplate for AT-SRG, White ABS, Single gang
4666 - AT-SRG-SGFP-SS - Faceplate for AT-SRG, Brushed Stainless Steel, Single gang
4663 - AT-SRG-AEK - AT-SRG Alarm Emulator Kit, c/w Emulator module and AT-SRG-S removal tool
4665 - AT-SRG-PSU-12 - Power Supply for AT-SRG-12/24, (230v to 12Vdc), c/w enclosure
4681 - AT-SRG-DGFP-W - AT-SRG Double Gang Faceplate Adaptor, ABS, Gloss White Finish
4682 - AT-SRG-DGFP-SS - AT-SRG Double Gang Faceplate Adaptor, Stainless Steel, Brushed Finish

TESTING GAS AND EQUIPMENT

4528 - AT-G-CALREG - Gas Regulator (0.3l/min), (Refrigerants Only)
5433 - AT-G-CALHOOD-SRG - Hose and hood kit (AT-SRG only)
4673 - AT-G-CYL-BMP - 110 Litre Gas Cylinder - For bump testing R410A, 20,000ppm in air (For AT-SRG)
4683 - AT-G-CYL-BMP - 110 Litre Gas Cylinder - For bump testing R32, 40% in air (For AT-SRG)

Important: All information, including illustrations, is believed to be reliable. Users, however, should independently evaluate the suitability of each product for their application. Aquilar Limited makes no warranty as to the accuracy or completeness of the information, and disclaims any liability regarding its use. The only obligations of Aquilar Limited are those in the Aquilar Standard Terms and Conditions of Sale for this product, and in no case will Aquilar Limited be liable for any incidental, indirect, or consequential damages arising from the sale, resale, use or misuse of the product. Specifications are subject to change without notice. In addition, Aquilar Limited reserves the right to make changes – without notification to Buyer – to processing or materials that do not affect compliance with any applicable specification.

AquiTron is a trademark of **AquiTron Limited**
Aquilar is a trademark of **Aquilar Limited**

Unit 30, Lawson Hunt Industrial Park,
 Broadbridge Heath, Horsham, West Sussex,
 RH12 3JR

+44 (0) 1403 216100

info@aquilar.co.uk

www.aquilar.co.uk